

ViewSonic® VX710 LCD Display

17" OPTISYNC® SLIM BEZEL DISPLAY



Brilliant color in a versatile, stylish display.

The 17" ViewSonic VX710 LCD display offers an ultra-stylish, slim-panel LCD that delivers dazzling clarity and rich colors at a price that will please you. Advanced digital technology and optimum 1280x1024 resolution gives you **BRILLANT IMAGES IN A LARGE DISPLAY AREA**. The high brightness, contrast ratio and ClearMotiv™ broadcast quality 16ms video response time bring your DVDs, games, video and photos to life with **REALISTIC COLOR, DETAIL AND ACTION**. You will also get precise screen to print colors with sRGB color management. The VX710 is the innovatively designed LCD that offers lots of extras for the discerning user without putting a big dent in your wallet.

Award-Winning Company

ViewSonic is the #1 best-selling monitor brand in the USA, delivering price and performance leadership.*



Stylish design, elegant display.

...OPTISYNC digital/analog inputs expand your connectivity

Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.

...Stylish slim-bezel design

The full 17" viewable screen in a thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.

...ClearMotiv technology

Super-fast 16ms video response delivers broadcast-quality full motion video at 62.5 fps.

...Ultra-high brightness and contrast

260-nit brightness (typ) and 450:1 contrast ratio (typ) for rich, detailed images.

...Full 17" viewable screen

...1280x1024 resolution

...OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

...VESA® 100mm wall mount compliant

...PC and Mac® compatible

...TCO'99 and ENERGY qualified



*Create a Total Desktop Solution
Add ViewMate® Collection accessories to your display for a complete desktop solution. Choose stylish mice and wireless keyboards, or turn that display into a TV with a TV/video processor.*

Cutting Edge

ViewSonic® 

the choice of professionals

ViewSonic® VX710 LCD Display

17" OPTISYNC® SLIM BEZEL DISPLAY



1. Sleek buttons control all major functions
2. Extended neck, floating head design
3. Space-saving slim-line panel design is only 2.4" thick
4. Slim bezel, attractive styling



Available colors:
Black & silver

17" COLOR LCD DISPLAY WITH CLEARMOTIV™ TECHNOLOGY

LCD	Type	17" Color TFT Active Matrix SXGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	450:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5
	Response Time	16ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
INPUT SIGNAL	Brightness	260 cd/m2 (typ)
	Panel Surface	Anti-glare
	Video Sync Frequency	RGB analog (75 ohms, 0.7 Vp-p); DVI-D (TMDS, 100 ohms) H/V separated (TTL), composite, sync-on-green F _H :24–82kHz, F _V :50–85Hz
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®**	Power Mac™ G3/G4 1280x1024
CONNECTOR	Analog	15-pin mini D-sub and DVI-D
	Power	3-pin AC plug, (CEE22)
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	35W (max)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, ViewMatch® color adjust (SRGB, 9300K, 6500K(default), 5400K, user color (RGB), input select (analog, digital), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, scaling, setup menu, language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), input priority, resolution notice, OSD position, OSD timeout, OSD background, touch tone, OSD pivot, memory recall
OPERATING CONDITIONS	Temperature	32°–104°F (0°–40°C)
	Humidity	10–90% (no condensing)
DIMENSIONS (W x H x D)	Physical	388mm x 438mm x 177mm (with stand)
		15.3" x 17.2" x 7.0" (with stand)
		388mm x 332mm x 62mm (without stand)
		15.3" x 13.1" x 2.4" (without stand)
WEIGHT	Net	11.0 lb. (5.0 kg) (with stand)
	Gross	16.8 lb. (7.6 kg) (with stand)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY, NOM, NEMKO/GS(covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), TCO'99, GOST-R 20 original copies hygienic, (SASO), PCBC, VCCI, BSMI, CCC, (PSB), (C-TICK), Argentina-S, PSE (power adapter), Green Mark
POWER MANAGEMENT		Meets TCO'99 and ENERGY standards
PACKAGE CONTENTS		LCD display, power cable, Quick Start Guide, ViewSonic Wizard CD, 15-pin VGA video cable
WARRANTY		One-year limited warranty on parts, labor and backlight for units purchased in the U.S. only. Three-year limited warranty on units purchased outside of the U.S.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic® 
the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Leading stand-alone, branded monitor by sales (CRT and LCDs combined: iSupply/Stanford Resources Monittrak® and Flat Panel Monittrak® 4Q04 Report) **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12291-008-01/05] VX710-1

For more product information, visit us on the web at ViewSonic.com

specifications